



# 2-unit to 5-unit Multi-split Indoor Units Specifications

## Wall-mounted type

Model name	Indoor unit	ASVG07KETE	ASVG09KETE	ASVG12KETE	ASVG14KETE
kW Class		2.0	2.5	3.5	4.0
Power Source		Single phase, ~230 V, 50 Hz			
Sound Pressure Level	Cooling	38/33/29/21	40/34/29/21	40/35/30/21	43/36/30/21
	Heating	41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24
Sound Power Level	Cooling	54	55	55	57
	Heating	56	57	58	59
Airflow Rate	Cooling	650/540/430/320	700/560/430/320	700/560/430/320	770/600/450/340
	Heating	720/580/460/330	750/610/470/330	770/640/520/330	800/660/520/340
Net Dimensions		mm 270 × 834 × 215	270 × 834 × 215	270 × 834 × 215	270 × 834 × 215
Weight		kg (lbs) 10 (22)	10 (22)	10 (22)	11 (24)
Connection Pipe Diameter	Liquid/Gas	mm 6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52

## Wall-mounted type

Model name	Indoor unit	ASVG07KETE ASVG07KETE-B	ASVG09KETE ASVG09KETE-B	ASVG12KETE ASVG12KETE-B	ASVG14KETE ASVG14KETE-B
kW Class		2.0	2.5	3.5	4.0
Power Source		Single phase, ~230 V, 50 Hz			
Sound Pressure Level	Cooling	38/33/29/21	40/34/29/21	40/35/30/21	43/36/30/21
	Heating	41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24
Sound Power Level	Cooling	54	55	55	57
	Heating	56	57	58	59
Airflow Rate	Cooling	650/540/430/320	700/560/430/320	700/560/430/320	770/600/450/340
	Heating	720/580/460/330	750/610/470/330	770/640/520/330	800/660/520/340
Net Dimensions		mm 295 × 950 (wall side: 840) × 230	295 × 950 (wall side: 840) × 230	295 × 950 (wall side: 840) × 230	295 × 950 (wall side: 840) × 230
Weight		kg (lbs) 11 (24)	11 (24)	11 (24)	11.5 (25)
Connection Pipe Diameter	Liquid/Gas	mm 6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52

## Wall-mounted type

Model name	Indoor unit	ASVG07KMCE	ASVG09KMCE	ASVG12KMCE	ASVG14KMCE
kW Class		2.0	2.5	3.5	4.0
Power Source		Single phase, ~230 V, 50 Hz			
Sound Pressure Level	Cooling	38/33/29/21	40/34/29/21	40/35/30/21	43/36/30/21
	Heating	41/35/31/22	42/36/31/22	42/38/33/22	44/39/33/24
Sound Power Level	Cooling	54	55	55	57
	Heating	56	57	58	59
Airflow Rate	Cooling	650/540/430/320	700/560/430/320	700/560/430/320	770/600/450/340
	Heating	720/580/460/330	750/610/470/330	770/640/520/330	800/660/520/340
Net Dimensions		mm 270 × 834 × 222	270 × 834 × 222	270 × 834 × 222	270 × 834 × 222
Weight		kg (lbs) 10 (22)	10 (22)	10 (22)	11 (24)
Connection Pipe Diameter	Liquid/Gas	mm 6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52

## Wall-mounted type

Model name	Indoor unit	ASVG24KMTE	ASVG24KMTE	ASVG24KMTE
kW Class		5.0	6.0	7.0
Power Source		Single phase, ~230 V, 50 Hz		
Sound Pressure Level	Cooling	45/40/35/29	48/40/35/29	49/40/35/29
	Heating	46/40/35/29	48/40/35/29	49/40/35/29
Sound Power Level	Cooling	61	62	65
	Heating	63	64	67
Airflow Rate	Cooling	980/810/640/510	1,080/810/640/510	1,170/810/640/510
	Heating	1,020/850/640/510	1,080/850/640/510	1,170/850/640/510
Net Dimensions		mm 280 × 980 × 240	280 × 980 × 240	280 × 980 × 240
Weight		kg (lbs) 12.5 (27)	12.5 (27)	12.5 (27)
Connection Pipe Diameter	Liquid/Gas	mm 6.35/12.70	6.35/12.70	6.35/12.70

## Floor

Model name	Indoor unit	AGYG09KVCA	AGYG12KVCA	AGYG14KVCA
kW Class		2.5	3.5	4.0
Power Source		Single phase, ~230 V, 50 Hz		
Sound Pressure Level	Cooling	39/34/28/22	42/38/30/22	44/38/31/22
	Heating	39/35/30/22	42/38/31/22	44/39/33/22
Sound Power Level	Cooling	52	55	56
	Heating	54	57	58
Airflow Rate	Cooling	530/440/380/270	600/440/380/270	650/440/380/270
	Heating	530/460/380/270	600/510/410/270	650/540/430/270
Net Dimensions		mm 600 × 740 × 200	600 × 740 × 200	600 × 740 × 200
Weight		kg (lbs) 14 (31)	14 (31)	14 (31)
Connection Pipe Diameter	Liquid/Gas	mm 6.35/9.52	6.35/9.52	6.35/9.52

## Ceiling

Model name	Indoor unit	ABYG18KRTA	ABYG22KRTA
kW Class		5.0	6.0
Power Source		Single phase, ~230 V, 50 Hz	
Sound Pressure Level	Cooling	38/36/33/31	42/37/34/31
	Heating	38/36/33/31	42/37/34/31
Sound Power Level	Cooling	53	57
	Heating	55	57
Airflow Rate	Cooling	860/790/710/650	900/790/710/650
	Heating	840/790/710/650	900/790/710/650
Net Dimensions		mm 235 × 1,080 × 705	235 × 1,080 × 705
Weight		kg (lbs) 24 (52)	24 (52)
Connection Pipe Diameter	Liquid/Gas	mm 6.35/12.70	6.35/12.70

## Compact Cassette Grid Type

Model name	Indoor unit	AUXG07KVLA	AUXG09KVLA	AUXG12KVLA	AUXG14KVLA	AUXG18KVLA	AUXG22KVLA
kW Class		2.0	2.5	3.5	4.0	5.0	6.0
Power Source		Single phase, ~230 V, 50 Hz					
Sound Pressure Level	Cooling	33/31/29/27	33/31/29/27	37/34/31/29	37/34/31/29	38/35/32/29	44/42/36/30
	Heating	34/32/29/27	34/32/29/27	37/34/31/29	37/34/31/29	43/38/34/30	45/43/40/33
Sound Power Level	Cooling	46	46	49	49	50	56
	Heating	47	47	49	49	55	57
Airflow Rate	Cooling	540/490/440/390	540/490/440/390	610/530/470/410	610/530/470/410	680/580/490/410	830/740/600/450
	Heating	540/490/440/390	540/490/440/390	610/530/470/410	610/530/470/410	790/680/580/450	860/760/600/530
Net Dimensions		mm 245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570	245 × 570 × 570
Weight		kg (lbs) 15 (33)	15 (33)	15 (33)	15 (33)	15 (33)	16 (35)
Panel		UTG-UFYF-W	UTG-UFYF-W	UTG-UFYF-W	UTG-UFYF-W	UTG-UFYF-W	UTG-UFYF-W
Connection Pipe Diameter	Liquid/Gas	mm 6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70	6.35/12.70

## Mini duct

Model name	Indoor unit	ARXG07KSLAP	ARXG09KSLAP	ARXG12KSLAP	ARXG14KSLAP	ARXG18KSLAP
kW Class		2.0	2.5	3.5	4.0	5.0
Power Source		Single phase, ~230 V, 50 Hz				
Sound Pressure Level	Cooling	29/26/24/23	29/26/24/23	31/27/25/23	31/27/25/23	35/30/27/23
	Heating	29/26/24/23	29/26/24/23	31/27/25/23	31/27/25/23	35/30/27/23
Sound Power Level	Cooling	52	54	55	55	58
	Heating	53	56	57	57	59
Airflow Rate	Cooling	550/440/390/360	600/450/400/360	650/490/430/360	650/490/430/360	800/640/530/360
	Heating	550/440/390/360	600/450/400/360	650/490/430/360	650/490/430/360	940/750/540/480
Net Dimensions		mm 198 × 700 × 450	198 × 700 × 450	198 × 700 × 450	198 × 700 × 450	198 × 900 × 450
Weight		kg (lbs) 15.5 (34)	15.5 (34)	15.5 (34)	15.5 (34)	18.5 (40)
Connection Pipe Diameter	Liquid/Gas	mm 6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70
External static pressure		Pa 0 to 30	0 to 30	0 to 30	0 to 30	0 to 50
Drain pump		Standard	Standard	Standard	Standard	Standard

## Slim duct

Model name	Indoor unit	ARXG07KLLAP	ARXG09KLLAP	ARXG12KLLAP	ARXG14KLLAP	ARXG18KLLAP
kW Class		2.0	2.5	3.5	4.0	5.0
Power Source		Single phase, ~230 V, 50 Hz				
Sound Pressure Level	Cooling	28/26/25/24	28/26/25/24	29/28/27/25	29/28/27/25	32/30/28/26
	Heating	28/26/25/24	28/26/25/24	29/28/27/25	29/28/27/25	32/30/28/25
Sound Power Level	Cooling	57	57	58	58	58
	Heating	57	57	58	58	58
Airflow Rate	Cooling	550/490/410/440	600/550/500/450	650/600/500/480	650/600/500/480	800/700/600/480
	Heating	550/490/410/440	600/550/500/450	650/600/500/480	650/600/500/480	940/880/820/750
Net Dimensions		mm 198 × 700 × 620	198 × 700 × 620	198 × 700 × 620	198 × 700 × 620	198 × 900 × 620
Weight		kg (lbs) 16 (35)	17 (37)	17 (37)	17 (37)	20 (44)
Connection Pipe Diameter	Liquid/Gas	mm 6.35/9.52	6.35/9.52	6.35/9.52	6.35/9.52	6.35/12.70
External static pressure		Pa 0 to 90	0 to 90	0 to 90	0 to 90	0 to 90
Drain pump		Standard	Standard	Standard	Standard	Standard

## Medium Static Pressure Duct

Model name	Indoor unit	ARXG22KMLB
kW Class		6.0
Power Source		Single phase, ~230 V, 50 Hz
Sound Pressure Level	Cooling	31/29/27/25
	Heating	31/29/27/25
Sound Power Level	Cooling	60
	Heating	62
Airflow Rate	Cooling	1,100/910/750/580
	Heating	1,100/910/750/580
Net Dimensions		mm 270 × 1,135 × 700
Weight		kg (lbs) 35 (77)
Connection Pipe Diameter	Liquid/Gas	mm 6.35/12.70
External static pressure		Pa 30 to 150
Drain pump		Standard